

**DIN 965 H**

Viti a metallo testa piana svasata croce
Countersunk flat head screws with cross recess H (Phillips)

dk	3,0	3,8	4,7	5,6	7,5	9,2	11,0	14,5
k max.	0,96	1,20	1,50	1,65	2,20	2,50	3,00	4,00

Length / Ø	M1,6	M2	M2,5	M3	M4	M5	M6	M8
3	♦♦	♦♦						
4	♦♦	♦♦	♦♦	♦♦				
5	♦♦	♦♦	♦♦	♦♦	♦♦			
6	♦♦	♦♦	♦♦	♦♦	♦♦	♦♦		
8	♦♦	♦♦	♦♦	♦♦	♦♦	♦♦	♦♦	
10	♦♦	♦♦	♦♦	♦♦	♦♦	♦♦	♦♦	♦♦
12	♦♦	♦♦	♦♦	♦♦	♦♦	♦♦	♦♦	♦♦
14	♦♦	♦♦	♦♦	♦♦	♦♦	♦♦	♦♦	♦♦
16	♦♦	♦♦	♦♦	♦♦	♦♦	♦♦	♦♦	♦♦
18		♦♦	♦♦	♦♦	♦♦	♦♦	♦♦	♦♦
20		♦♦	♦♦	♦♦	♦♦	♦♦	♦♦	♦♦
22				♦♦	♦♦	♦♦	♦♦	♦♦
25				♦♦	♦♦	♦♦	♦♦	♦♦
30				♦♦	♦♦	♦♦	♦♦	♦♦
35				♦♦	♦♦	♦♦	♦♦	♦♦
40				♦♦	♦♦	♦♦	♦♦	♦♦
45				♦♦	♦♦	♦♦	♦♦	♦♦
50				♦♦	♦♦	♦♦	♦♦	♦♦
55				♦♦	♦♦	♦♦	♦♦	♦♦
60				♦♦	♦♦	♦♦	♦♦	♦♦
65				♦♦	♦♦	♦♦	♦♦	♦♦
70					♦♦	♦♦	♦♦	♦♦
75					♦♦	♦♦	♦♦	♦♦
80					♦♦	♦♦	♦♦	♦♦
85					♦♦	♦♦	♦♦	♦♦
90					♦♦	♦♦	♦♦	♦♦
95					♦♦	♦♦	♦♦	♦♦
100					♦♦	♦♦	♦♦	♦♦
SU	1000	1000	1000	1000	1000 ≥ 25 500 ≥ 70 200	500 ≥ 25 200	200 ≥ 35 100	100

Legenda tipologia materiale

♦ A1 / ♦ A2 / ♦ A4